

**PROFESSIONAL M60  
Low Carbon**

MONOCRYSTALLINE 285-295 WP

**Certified sustainable  
manufacturing**

Sustainable manufacturing certified by Certisolis

Carbon emissions during production are 50% lower than industry average

**low  
CO<sub>2</sub>**



**Optimized for  
performance**

PID-free monocrystalline high performance solar cells

Antireflective-coated solar glass

Low-light optimized

Positively classified -0/+4.99 Wp

Industry-leading NMOT values

**Highest quality  
standards**

Manufactured according to  
DIN EN ISO 9001:2015  
DIN EN ISO 14001:2015  
BS OHSAS 18001:2007

PV-module type approval according to IEC 61215:2016 <sup>3</sup>

PV-module safety qualification according to IEC 61730:2016 <sup>3</sup>

**Guaranteed  
performance <sup>1</sup>**

26 years of linear performance guarantee

12 years product guarantee, optional extension to 25 years

Total Care for the entire system (optional)

<sup>1</sup> For detailed information please consult the CS Wismar GmbH warranty conditions

<sup>2</sup> See backside for detailed test loads

<sup>3</sup> Subject to recertification

# PROFESSIONAL 285 | 290 | 295 M60 LOW CARBON

## Performance STC

Under standard Test Conditions STC:  
1000 W/m<sup>2</sup>; spectrum AM 1.5;  
Cell temperature 25°C  
Measurement tolerance STC:  
P<sub>mpp</sub> ±3%; I<sub>sc</sub> ±10%; U<sub>oc</sub> ±10%


Nominal Power P <sub>mpp</sub> (Wp)	285	290	295
Open Circuit Voltage U <sub>oc</sub> (V)	39,33	39,48	39,64
Voltage U <sub>mpp</sub> (V)	32,01	32,37	32,66
Short Circuit Current I <sub>sc</sub> (A)	9,54	9,63	9,71
Current I <sub>mpp</sub> (A)	8,90	8,95	9,02
Efficiency η (%)	17,0	17,3	17,6

Reduction of module efficiency at reduction from 1000 W/m<sup>2</sup> to 200 W/m<sup>2</sup>: 2,3% ± 0,5% (relative)


## Performance NMOT

Nominal operating temperature of module  
800 W/m<sup>2</sup>, NMOT, AM 1.5

Nominal Power P <sub>mpp</sub> (Wp)	222	226	229
Open Circuit Voltage U <sub>oc</sub> (V)	36,52	36,66	36,81
Voltage U <sub>mpp</sub> (V)	31,23	31,55	31,81
Short Circuit Current I <sub>sc</sub> (A)	7,72	7,79	7,86
Current I <sub>mpp</sub> (A)	7,11	7,15	7,21



measurements in mm



**clamping area**  
 approved up to 2.400 Pa  
 approved up to 5.400 Pa  
 no contact between junction box and mounting profile permitted in this area.

## Other Technical Specification

Max. system voltage	1000 V
Weight	19.5 ± 0.5 kg
Reverse Current Load I <sub>R</sub>	15 A
Junction box	IP 67 with 3 bypass diodes
Connectors	IP 67, MC4
Fire rating	class C
Operating temperature	-40°C ... +85°C
Design load: snow	5.400 Pa *
Max test load	8.100 Pa
Design load: wind	2.400 Pa *
Max test load	3.600 Pa

\* safety factor 1.5

## Thermal Properties

TC P <sub>mpp</sub>	-0.41 %/K
TC U <sub>oc</sub>	-0.31 %/K
TC I <sub>sc</sub>	0.045 %/K
NMOT	45 +/- 2 °C

## Material Used

No. of cells	60 cells
Type of cells	monocrystalline
Front	hardened solar glass
Frame	anodized aluminium
Frame height	40 mm

